

PRODUCT SPECIFICATION

SAFETYWARE Vertical Fold-Flat FFP2 Particulate Respirator

- FFP2 disposable particulate respirators are approved for use against oil & non oil particulate aerosols.
- These respirator provide filtration of at least 94% efficiency.
- Features:
 - Polypropylene (PP) inner layer provides the most intimate touch to your face.
 - Head strap buckle to adjust the length of head strap for various facial sizes.
 - Adjustable hidden nose clip helps provide a custom & secure fit.
 - Cool latex-free textile head strap for comfortable wearing.
 - Continuous loop head strap design can allow to hang the mask around the neck when not in use.
 - Ultrasonic welded to avoid fluffy open layer around the edges.
 - Contour design ensures the compatibility of glasses/goggles and reduces fogging.
 - Fold-flat design offers convenient storage and portability.
 - Individual packaging helps protect the respirator from contamination before use.
- 4802V & 4802AV with exhalation valve to reduce the heat build-up inside the respirator.
- 4802AV is with activated carbon layer to protect against nuisance acid gas and organic vapor.

APPLICATIONS

- Textile Industry
- Craft Work
- Iron & Steel Industry
- Mining
- Underground Civil Engineering
- Welding
- Woodworking
- Cutting & Casting of Metals
- Hospital
- Laboratory
- Disease Control
- Chemical

4802 Series



ITEM CODE

ITEM CODE	DESCRIPTION
4802	SAFETYWARE Vertical Fold-Flat FFP2 Particulate Respirator
4802V	SAFETYWARE Vertical Fold-Flat FFP2 Particulate Respirator with Valve
4802AV	SAFETYWARE Vertical Fold-Flat FFP2 AG/OV Particulate Respirator with Valve

SAFETYWARE SDN. BHD. (632971-X)

Plot 237, Lengkok Perindustrian Bukit Minyak 3,
Bukit Minyak Industrial Estate,
14100 Simpang Ampat, Penang, Malaysia

Tel : +604-5023 882 | Fax : +604-5081 882
www.safetyware.com | info@safetyware.com

It is the product users' responsibility to conduct all the appropriate evaluations & testing to determine the suitability of SAFETYWARE products for use in a particular environment or purpose. SAFETYWARE disclaims all warranties other than as expressly provided.

Date created: 02/12/2020

Revision: 06

Date revised: 04/09/2023

PRODUCT SPECIFICATION

TECHNICAL DATA

MATERIAL	Outer layer : Non-woven Polypropylene (Hydrophobic) Filter media : High filtration efficiency melt-blown Inner layer : Non-woven Polypropylene (Hydrophilic) Activated Carbon (for 4802AV)
STANDARD	SIRIM : BS EN 149:2001+A1:2009 AS/NZS 1716:2012 4802 : FFP2 NR D (JKKP/2021/12-01/06/00041/0001) 4802V : FFP2 NR (JKKP/2021/12-01/06/00043/0001) 4802AV : FFP2 NR (JKKP/2021/12-01/06/00042/0001)
SHELF LIFE	3 years from manufacture date
PACKAGING	20 pcs/ box, 12 boxes/ carton
CARTON DIMENSION	4802 : 370 mm (L) x 345 mm (W) x 272 mm (H) 4802V & 4802AV : 545 mm (L) x 345 mm (W) x 370 mm (H)

SAFETYWARE SDN. BHD. (632971-X)

Plot 237, Lengkok Perindustrian Bukit Minyak 3,
Bukit Minyak Industrial Estate,
14100 Simpang Ampat, Penang, Malaysia

Tel : +604-5023 882 | Fax : +604-5081 882
www.safetyware.com | info@safetyware.com

It is the product users' responsibility to conduct all the appropriate evaluations & testing to determine the suitability of SAFETYWARE products for use in a particular environment or purpose. SAFETYWARE disclaims all warranties other than as expressly provided.

Date created: 02/12/2020

Revision: 06

Date revised: 04/09/2023